

Saddle-stitch  
Finisher-C2Multiposition Auto  
Stapler Finisher-C1Stapler Stacker  
Finisher-E1Cassette  
Feeding UnitsCassette  
Feeding Units

Paper Deck-B1

**imageRUNNER 400S Specifications**

|                                                |                                                                                                                        |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Type:                                          | Digital Multifunction Imaging System                                                                                   |
| Imaging System:                                | Laser Dry Electrostatic Transfer                                                                                       |
| Developing System:                             | Dry Monocomponent Toner Projection                                                                                     |
| Image Server Memory:                           | Standard 128MB                                                                                                         |
| First-print Speed:                             | 6 Seconds from ADF or Less                                                                                             |
| Warm-up Time:                                  | 92 Seconds or Less                                                                                                     |
| Multipage Speed:                               | 40 ppm                                                                                                                 |
| Resolution:                                    | 600 dpi x 600 dpi                                                                                                      |
| Interpolated Resolution:                       | 1200 dpi x 600 dpi                                                                                                     |
| Halftone:                                      | 256 Gradations of Gray (Continuous-tone)                                                                               |
| Scanner:                                       | CCD, 600-dpi Resolution                                                                                                |
| Document-handling:                             | Automatic Document Feeder                                                                                              |
| Automatic Document Feeder Capacity:            | 50 Sheets (DADF-A1),<br>30 Sheets (DADF-B1)                                                                            |
| Max. Original Size:                            | 11" x 17" (Ledger)                                                                                                     |
| Output Sizes                                   |                                                                                                                        |
| Cassette:                                      | Statement to Ledger                                                                                                    |
| Bypass:                                        | Statement to Ledger                                                                                                    |
| Paper Supply                                   |                                                                                                                        |
| Standard:                                      | Dual Front-loading Cassettes<br>(500 Sheets Each)<br>50-sheet Stack Bypass                                             |
| Optional:                                      | 1,000-sheet Two-cassette Feeder<br>2,000-sheet Four-cassette Feeder<br>3,500-sheet Paper Deck<br>(Total: 5,550 Sheets) |
| Output Options:                                | Stapler Stacker Finisher<br>Multiposition Auto Stapler<br>Saddle-stitch Finisher<br>Standard Automatic Trayless        |
| Duplexing:                                     |                                                                                                                        |
| Duplexing Magnification Reduction/Enlargement: | 25% to 800% in 1% Increments                                                                                           |
| Multiple Copies:                               | 1 to 999                                                                                                               |
| Paper Weights:                                 | 13 lb. to 32 lb.                                                                                                       |
| <b>Supplies</b>                                |                                                                                                                        |
| Drum:                                          | OPC – Estimated Yield:<br>55,000 Impressions                                                                           |
| Duty Cycle:                                    | 150,000 Impressions Per Month                                                                                          |

**ACCESSORIES****Automatic Document Feeder (DADF-A1)**

|                       |                           |
|-----------------------|---------------------------|
| Acceptable Originals: | Statement to Ledger       |
| Capacity:             | 50 Sheets (Letter/20 lb.) |
| Max. Paper Weight:    | Up to 28 lb.              |

**Automatic Document Feeder (DADF-B1)**

|                       |                     |
|-----------------------|---------------------|
| Acceptable Originals: | Statement to Ledger |
| Capacity:             | 30 Sheets           |
| Max. Paper Weight:    | Up to 28 lb.        |

**Cassette Feeding Units**

|                      |                                                |
|----------------------|------------------------------------------------|
| Number of Cassettes: | Two or Four Cassettes                          |
| Paper Capacity:      | 1,000 or 2,000 Sheets<br>(Statement to Ledger) |
| Paper Weights:       | Up to 22 lb. Bond                              |

**Paper Deck-B1**

|                 |                       |
|-----------------|-----------------------|
| Paper Capacity: | 3,500 Sheets (Letter) |
| Paper Weights:  | Up to 22 lb. Bond     |

**Stapler Stacker Finisher-E1**

|                               |                       |
|-------------------------------|-----------------------|
| Number of Trays:              | One Tray              |
| Tray Capacity:                | 1,000 Sheets (Letter) |
| Staple Position/<br>Capacity: | Top Corner/30 Sheets  |

**Multiposition Auto Stapler-C1**

|                    |                                                           |
|--------------------|-----------------------------------------------------------|
| Number of Trays:   | Four Trays, Including Interrupt Tray                      |
| Tray Capacity      |                                                           |
| Top Tray:          | 300 Sheets (Letter)                                       |
| Middle Tray:       | 750 Sheets (Letter)                                       |
| Lower Tray:        | 200 Sheets (Letter)                                       |
| Staple Positions:  | Multiposition Stapling<br>(1) Top Corner; (2) Side Margin |
| Stapling Capacity: | 50 Sheets                                                 |

**Saddle-stitch Finisher-C2**

|                  |                                                            |
|------------------|------------------------------------------------------------|
| Number of Trays: | Five Trays, including Interrupt<br>and Saddle-stitch Trays |
| Tray Capacity    |                                                            |
| Top Tray:        | 300 Sheets (Letter)                                        |

|                     |                     |
|---------------------|---------------------|
| Middle Tray:        | 750 Sheets (Letter) |
| Lower Tray:         | 200 Sheets (Letter) |
| Saddle-stitch Tray: | 300 Sheets          |

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| Staple Positions:  | Multiposition Stapling<br>(1) Top Corner; (2) Side Margin;<br>(3) Saddle-stitch |
| Stapling Capacity: | 50 Sheets (Saddle-stitch: 15 Sheets)                                            |

**Saddle-stitch Specifications**

|                     |                            |
|---------------------|----------------------------|
| Total Sides Imaged: | 60 Total Sides (15 Sheets) |
| Total Sets:         | 10 Total Sets              |
| Folding:            | V-folding Standard         |

**Network Print Controller**

|                   |                                             |
|-------------------|---------------------------------------------|
| Type:             | Embedded Print/Network                      |
| Processor:        | Pentium® III 500MHz                         |
| RAM:              | 128MB                                       |
| PDL Support:      | Adobe PostScript 3 – PCL 5e, PCL 6          |
| PostScript Fonts: | 136 TrueType®                               |
| PCL Fonts:        | 80 Fonts, 32 Resident and<br>Bar-code Fonts |

|                     |                                       |
|---------------------|---------------------------------------|
| Hard Disk:          | 10GB                                  |
| Optimized Features: | Continuous Print™<br>RIP-While-Print® |

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Printer Interface |                                                                |
| Ports:            | Bi-Directional Centronics<br>Ethernet<br>Token Ring (Optional) |
| Topology:         | 10/100 Mbps Ethernet<br>4/16 Mbps Token Ring                   |
| Speed:            |                                                                |

|                               |                                                |
|-------------------------------|------------------------------------------------|
| Protocols Supported           |                                                |
| Ethernet:                     | TCP/IP, IPX/SPX, EtherTalk®                    |
| Token Ring:                   | TCP/IP, IPX/SPX                                |
| Network Interface Connections |                                                |
| Ethernet:                     | 10/100Base-TX (RJ-45), 10Base-5<br>RJ-45, DB-9 |
| Token Ring:                   |                                                |

Additional options, including faxing and scanning, are available.  
Please contact your local Canon-authorized Dealer for details.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR certification are registered U.S. trademarks. IPX/SPX is a trademark of Novell, Inc. AppleTalk, Macintosh, EtherTalk, and TrueType are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. UNIX is a registered trademark of the Open Group in the U.S. and other countries. Pentium is a registered trademark of Intel Corporation. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. Adobe and PostScript are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. RIP-While-Print is a registered trademark of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and certain other foreign jurisdictions. Continuous Print is a trademark of Electronics for Imaging, Inc. Canon and NetSpot are registered trademarks, and IMAGERUNNER, the GENUINE logo, and Canon Know How are trademarks of Canon Inc. IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

All specifications subject to change without notice.

**Canon** KNOW HOW™

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

0032W540

0802-iR400S-40M



PRINTED ON RECYCLED  
PAPER IN THE U.S.A.



Money Isn't All You're Saving

