






Views

Tilt and Transform

Specifications

Copyright © 2014 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2014 - 12 Rev. A01 Regulatory model: W07C | Type: W07C002 Computer model: Inspiron 2350








Back

Front



Intel RealSense 3D Camera

Allows to capture and stream three-dimensional images. Enables enhanced interactivity during video conferencing, online gaming, and so on.

OR

1

Camera

Allows you to video chat, capture photos, and record videos.

2 Microphones (2)


Provides high-quality digital sound input for audio recording, voice calls and so on.

3 Camera-status light

Turns on when the camera is in use.



1




Back

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.



Right







Back

1 Brightness/Volume-control buttons (2)

When not connected to an external input video device (PC mode), press to increase or decrease the brightness of the screen.

When connected to an external input video device (AV mode), press to increase or decrease the volume.

2 Input source selection button/screen-off button

Press and release to switch between the input source. Press and hold to turn off the display.

3 Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

4 Power button

Press to turn on the computer if it is turned off or in Sleep state. Press to put the computer in Sleep state if it is turned on. Press and hold for 10 seconds to force shut-down the computer.

NOTE: You can customize the power-button behaviour in Power Options. For more information, see *Me and My Dell* at **dell.com/support**.

5 Media-card reader


Reads from and writes to media cards.

6 USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

7 Headset port

Connect a power adapter to provide power to your computer.





Back







Back



1 Audio-out port

Connect audio-output devices such as speakers, amplifiers, and so on.

2 Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

3 USB 2.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

4 HDMI-out port

Connect a TV or other HDMI-in enabled devices. Provides video and audio output.

5 HDMI-in port

Connect a gaming console, Blu-ray player, or other HDMI-out enabled devices.

6 Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.



Tilt and Transform

Tilt




Transform



Dimensions and Weight

	Inspiron 2350 with Intel RealSense 3D Camera	Inspiron 2350
Height	430.83 mm (16.96 in)	418.86 mm (16.49 in)
Width	582.98 mm (22.95 in)	569.38 mm (22.42 in)
Depth	240.96 mm (9.49 in)	241 mm (9.49 in)
Weight (maximum):	Touch only	Touch Non-touch
Without stand	8.06 kg (17.77 lb)	7.25 kg (15.98 lb) 6.24 kg (13.76 lb)
With stand	9.49 kg (20.92 lb)	8.63 kg (19.03 lb) 7.62 kg (16.80 lb)

NOTE: The weight of your computer varies depending on the configuration ordered and the manufacturing variability.



System Information

Computer model	Inspiron 2350
Processor	Intel Core i3
	Intel Core i5
	Intel Core i7
L2 cache	512 KB
L3 cache	Up to 6 MB
Chipset	Intel HM87






Memory

Slot	Two SODIMM slots
Туре	Dual-channel DDR3L
Speed	Up to 1600 MHz
Configurations supported	4 GB, 8 GB, 12 GB, and 16 GB



Ports and Connectors

External:	
Network	One RJ45 port
USB	Two USB 2.0 ports
	Four USB 3.0 ports
Audio	One headset port
	One audio-out port
Video	HDMI-in port
	HDMI-out port
Internal:	
Mini Card	One half mini card slot for WLAN and Bluetooth
	One full-mini card slot for mSATA drive



Communications

Ethernet

Wireless

10/100/1000 Mbps Ethernet LAN integrated on system board


- Wi-Fi 802.11b/g/n
- Wi-Fi 802.11ac
- Bluetooth 4.0 LE
- Intel WiDi
- Miracast (only on computers shipped with 802.11b/g/n wireless card)





Video


Controller:	
Integrated	Intel HD Graphics 4600
Discrete	AMD Radeon HD 8690 A
Memory:	
Integrated	System shared memory
Discrete	2 GB GDDR5





Audio


Controller	Realtek ALC290Q audio with Waves MaxxAudio 5
Speaker	Two 4-watt speakers
Microphone	Digital microphones in camera assembly
Volume controls	Program menus





Storage

Interface	SATA 6 Gbps
Hard drive	One 2.5-in
mSATA	One mSATA card




Media-Card Reader

Туре

Cards supported

One 8-in-1 slot


- SD card
- SD Extended Capacity (SDXC) card
- SD High Capacity (SDHC) card
- MultiMediaCard (MMC)
- Memory Stick (MS)
- Memory Stick PRO
- Memory Stick PRO-HG
- Memory Stick XC





Display


	Inspiron 2350 with Intel RealSense 3D Camera	Inspiron 2350
Туре	23.8-inch full HD (Touch)	23-inch full HD (Touch)23-inch full HD (non touch)
Resolution (maximum)	1920 x 1080	1920 x 1080
Dimensions:		
Height	361.18 mm (14.22 in)	347.62 mm (13.69 in)
Width	582.98 mm (22.95 in)	569.38 mm (22.42 in)
Refresh rate	60 Hz	60 Hz
Viewing angle	178 degrees	178 degrees
Pixel pitch	0.2745 mm	0.2652 mm
Controls	Brightness can be controlled through the brightness-control buttons	





Stand

Tilt	–5 to 90 degrees (flat)
Width	267.30 mm (10.52 in)
Depth	240.96 mm (9.49 in)
Weight:	
Basic	1.07 kg (2.36 lb)
Articulating	1.17 kg (2.58 lb)





Camera


	•	biron 2350 alSense 3D Camera	Inspiron 2350
	Photo/Video	Infrared	Photo/Video
Resolution (maximum)	1920 x 1080 (FHD)	640 x 480 (VGA)	1920 x 1080 (FHD) with Skype certification
Aspect ratio	16:9	4:3	16:9
Diagonal viewing angle	77 degrees	90 degrees	66 degrees
Frame rate (varies with resolution)	30/60/120 fps	30/60/120 fps	30 fps
Field of view	77 x 43 x 70 degrees	90 x 59 x 73 degrees	N/A
Depth data types	N/A	Depth, texture mapping,	N/A
		infrared, and word mapping	
Still image	2 megapixels		2 megapixels
Effective range	0.20 m–1.20 r	0.20 m–1.20 m	
Effective range for gestures	• 20 cm-55 cm	(FHD)	N/A
	 20 cm-60 cm 	i (VGA)	
Effective range for face tracking		ng: 35 cm–120 cm ng: 35 cm–70 cm	N/A





Power Adapter

Туре:	 150 W 180 W
Input voltage	100 VAC-240 VAC
Input frequency	50 Hz-60 Hz
Input current	2.50 A
Output current (continuous):	
150 W	7.70 A
180 W	9.93 A
Rated output voltage	19.50 VDC
Temperature range:	
Operating	0°C to 40°C (32°F to 104°F)
Storage	-40°C to 70°C (-40°F to 158°F)



Computer Environment

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0°C to 40°C (32°F to 104°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G [†]	160 G [‡]
Altitude (maximum)	-15.2 m to 3048 m (-50 ft to 10,000 ft)	-15.2 m to 10,668 m (-50 ft to 35,000 ft)

* Measured using a random vibration spectrum that simulates user environment.

† Measured using a 2 ms half-sine pulse when the hard drive is in use.

‡ Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.

