


Elo 3239L 32-inch Open-Frame Touch Monitor



Model	3239L
Display	32.0" diagonal
Aspect Ratio	16:9, active matrix TFT LCD
Useful Screen Area	Horizontal: 27.5" (698 mm) Vertical: 15.4" (392 mm)
Native (Optimal) Resolution	1366 x 768
Other Supported Resolutions	640x480 @ 60Hz 800x600 @ 56Hz, 60Hz 1024x768 @ 60Hz 1280x960 @ 60 Hz 1280x1024 @ 60Hz 1360x768 @ 60 Hz 1366x768 @ 60 Hz 1440x900 @ 60 Hz 1600x1200 @ 60 Hz 1680x1050 @ 60 Hz
Colors	16.7 million
Brightness (Typical)	LCD panel: 450 nits IntelliTouch: 405 nits
Response Time - Total (Typical)	8 msec
Viewing Angle (Typical) 	Horizontal: ±89° or 178° total Vertical: ±89° or 178° total
Contrast Ratio (Typical)	3000:1
On-Screen Display (OSD)	Controls (back): menu, up, down, select Settings: automatic adjustment, contrast, brightness, H/V position, clock, phase, color temperature, input video select, OSD H/V position, OSD timeout, recall color, recall default, sharpness, display information

	Languages: English, French, Italian, German, Spanish, Japanese, Traditional Chinese, Simplified Chinese Lockouts: power, user controls
--	---

Power

Input Video Format	Analog VGA, DVI video (Asia and EMEA models without DVI)
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type, DVI-D connector
Input Frequency	Horizontal: 30-75 kHz Vertical: 48-63 Hz
Power Supply	Internal AC
Input Voltage	AC: 100–240 VAC, 50/60Hz
Input Connector	AC: IEC 60320 C6
Power Consumption	145W typical; 190W max. at 110V/60Hz input)

Dimensions

Monitor Dimensions	Width: 30.9" (784 mm) Depth: 4.3" (110 mm) Height: 18.7" (474 mm)
Shipping Box Dimensions	Width: 39.4" (1000 mm) Depth: 26.8" (680 mm) Height: 13.4" (340 mm)

Weights

Weight	Actual: 38.1 lb (17.3 kg) Shipping: 47.6 lb (21.6 kg)
---------------	--

Environmental

Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (noncondensing)	Operating: 20%-80% Storage: 10%-90%

Other

Form Factor	Open-frame
Enclosure Color	Black
MTBF	50,000 hours demonstrated
Mounting Options	200mm x 100mm VESA mount Mounting brackets included
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD