

# TS Series 65" Interactive LCD Display

## Series

Series	Series TS
--------	-----------

## Display

Screen Size	65"
-------------	-----

Panel Technology	CCFL Backlit
------------------	--------------

Resolution	1920x1080
------------	-----------

Aspect Ratio	16:9
--------------	------

Brightness	500 cd/m2
------------	-----------

Contrast Ratio (Typical)	5000:1
--------------------------	--------

Contrast Ratio (Dynamic)	10000:1
--------------------------	---------

Viewing Angle (H/V)	178/178
---------------------	---------

## Power

Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
--------------	--------------------------------------

Power Consumption (Typical/Max)	430W/470W
---------------------------------	-----------

Power Consumption (Standby)	Under 2 W
-----------------------------	-----------

## Features

Special	Embedded Touch (Optional), Lamp Error Detection, Brightness Sensor, Anti Retention, Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Video Wall (5x5), Pivot Display, Button Lock, Smart Scheduling, Smart FAW update (eboard software included, landscape orientation only)
---------	--

Multimedia Speakers	Built in Speaker (15W + 15W)
---------------------	------------------------------

## Dimensions

Without Stand (W x H x D)	61.2" x 36.4" x 5.4"
---------------------------	----------------------

Packaging (W x H x D)	66.5" x 41.7" x 17.7"
-----------------------	-----------------------

## Weight

Set	154 lb
-----	--------

Package	176.9 lb
---------	----------

## Accessories

Wall Mount	WMN - 7070D
------------	-------------

Stand	STN- L65D
-------	-----------

## Green Management

RoHS Compliant	RoHS Compliant
----------------	----------------

## Mechanical Specs

VESA Mount	800 x 400 mm VESA Mount Standard
------------	----------------------------------

## Operation

Operating Temperature	0°C ~ 40°C
-----------------------	------------

Operating Humidity	10 - 80%
--------------------	----------